ENGINEERING PHARMACEUTICAL INNOVATION



DCS Development Systems in a Virtualized Environment







Presenter

Scott Thompson – Systems Consultant











Introduction

- Challenges in supporting multiple DCS revisions
- Our Solution
- Benefits
- Your Benefits







Challenges in Supporting Multiple Systems

- Flexibility
 - Support many different customer systems
 - Currently have ~80 Customer DCS databases loaded
 - ~10 Envox NT/Control Desktop databases
 - Support many different DCS revisions
 - 16 different DCS versions
 - 5 different Windows versions (including service packs)
 - 2+ new systems in development (two more Windows Versions, Windows 7 & Server 2008 SP2)







Challenges in Supporting Multiple Systems

- Faster Turnaround
 - Reset back to base-line after testing
- Robustness
 - How fast can the system be recovered if something breaks







Challenges in Supporting Multiple Systems – Physical Hardware

- Flexibility
 - Support many different customer systems
 - Currently have ~80 Customer DCS databases loaded
 - ~10 Envox NT/Control Desktop databases

Large number of computers







Challenges in Supporting Multiple Systems – Physical Hardware

- Flexibility
 - Support many different DCS revisions
 - 16 different DCS versions
 - 5 different Windows versions (including service packs)
 - 2+ new systems in development (two more Windows Versions, Windows 7 & Server 2008 SP2)

At least 18 computers







Challenges in Supporting Multiple Systems – Physical Hardware

- Faster Turnaround
 - Reset back to base-line after testing

Restore from image (1-3 hours)

- Robustness
 - How fast can the system be recovered if something breaks

Restore from image (1-3 hours)







- Will the development software work on a virtual computer?
- How stable will it be?
- ESX and ESXi don't support USB devices, how do I get the USB hardlock connected?
- How do I best save the system already running on the hardware I'm re-using?







- Will the development software work on a virtual computer?
- How stable will it be?
- ESX and ESXi don't support USB devices, how do I get the USB hardlock connected?ESX(i) 4.1
- How do I best save the system already running on the hardware I'm re-using?







- Will the development software work on a virtual computer?
 - In our case Yes
- How stable will it be?
 - Similar to physical machine installation
- ESX and ESXi don't support USB devices, how do I get the USB hardlock connected?
 - USB Over Network ESX(i) 4.1
- How do I best save the system already running on the hardware I'm re-using?
 - VMWare Converter







- Still need a Windows computer to manage the ESX(i) computers
- The USB Over Network server needs to be installed on a Windows or Linux computer







Challenges in Supporting Multiple Systems – Virtualized

- Flexibility
 - Support many different customer systems
 - Currently have ~80 Customer DCS databases loaded
 - ~10 Envox NT/Control Desktop databases

5 physical computers, many virtual







Challenges in Supporting Multiple Systems – Virtualized

- Flexibility
 - Support many different DCS revisions
 - 16 different DCS versions
 - 5 different Windows versions (including service packs)
 - 2+ new systems in development (two more Windows Versions, Windows 7 & Server 2008 SP2)

5 physical computers, many virtual







Challenges in Supporting Multiple Systems - Virtualized

- Faster Turnaround
 - Reset back to base-line after testing

Restore to snapshot (5 minutes)

- Robustness
 - How fast can the system be recovered if something breaks

Restore to snapshot (5 minutes)







- 73 Servers (real and virtual)
 - 16 physical stand-alone servers (application dedicated)
 - 5 VMWare Servers (running on Server 2003)
 - 17 virtual machines
 - 4 ESXi v4.x machines
 - 31 virtual machines
 - 21 Pro+ (600 DST 12,000 DST)
 - 2 Batch Executives (for ~12,000 DST systems each)
 - 2 Batch Historians
 - Iconics Server
 - Mimic Server
 - Thin Manager Server
 - Syncade Server
 - Control Desktop Server (Windows NT 4)
 - Virtual CIOC







- Used existing hardware
- Upgraded RAM for three ESXi servers
- Additional hardware cost to add 19 virtual machines was ~\$340.







- 19 licenses for Server 2003/Server 2008
 - \$14,440
 - If buying physical machine, cost is buried in hardware cost
- VMWare ESXi
 - \$0
- Windows TS CALS
 - \$0 (pre-existing)
- USB Over Network
 - \$600 for 8 USB devices







- 19 licenses for Server 2003/Server 2008
 - \$14,440
 - If buying physical machine, cost is buried in hardware cost
- VMWare ESXi
 - \$0
- Windows TS CALS
 - \$0 (pre-existing)
- USB Over Network
 - \$600 for 8 USB devices







REM Benefits

- Reduced hardware footprint
 - 3 vs. 19
- Reduced power usage
 - 750W vs. 4750W
- Reduced A/C load
 - 8,091 BTU/hr vs. 51,243 BTU/hr
 - < 1 ton vs. 5 ton
- Increased flexibility
 - Computers that support NT hard to find
- Decreased setup time for new system
 - Can have a new virtual computer on-line < 1hr.







REM Benefits

- Lower testing risk
 - Take snapshots before installing something untested or installing updates
 - Easily revert to the snapshot if something doesn't work correctly







Large Plant DCS Development System Example - Physical Hardware

- Configuration Server, Batch/Continuous Historian, Batch Executive, Operator Station RT Server, Virtual Controllers Application Station (3)
 - Configuration Server 1 R710 \$7200
 - Historian, Batch Executive 2 R710 \$14400
 - Operator Station RT Server 1 R710 \$7200
 - Virtual Controllers 3 R710 \$21600
 - \$50,400







Large Plant DCS Development System Example - Virtualized

- Configuration Server, Batch/Continuous Historian, Batch Executive, Operator Station RT Server, Virtual Controllers Application Station (3)
 - Host Server \$7200
 - 16 GB RAM upgrade \$1400
 - Configuration Server 1 OS License \$750
 - Historian, Batch Executive 2 OS Licenses \$1500
 - Operator Station RT Server 1 OS License \$750
 - Terminal Server License (4 users) \$320
 - Virtual Controllers 3 OS Licenses \$2350
 - \$14,270







	Without Virtualization	With Virtualization	Savings
Cost	\$50,400		
Power Consumption	4,788 W		
Heat Dissipation	16,000 BTU/hr (1.36 tons)		







	Without Virtualization	With Virtualization	Savings
Cost	\$50,400	\$14,270	
Power Consumption	4,788 W	700 W	
Heat Dissipation	16,000 BTU/hr (1.36 tons)	2,334 BTU/hr (.19 tons)	







	Without Virtualization	With Virtualization	Savings
Cost	\$50,400	\$14,270	\$36,130 one-time
Power Consumption	4,788 W	700 W	\$2,100 per year (at \$0.06 per kWH)
Heat Dissipation	16,000 BTU/hr (1.36 tons)	2,334 BTU/hr (.19 tons)	\$697 per year (assumes very efficient A/C system, 0.33 K-factor)







	Without Virtualization	With Virtualization	Savings
Cost	\$50,400	\$14,270	\$36,130 one-time
Power Consumption	4,788 W	700 W	Reduce Carbon Footprint
Heat Dissipation	16,000 BTU/hr (1.36 tons)	2,334 BTU/hr (.19 tons)	Reduce Carbon Footprint







Questions?





